



2010 **Street** Division Rules

D. System Requirements

1. Enclosure must be mounted behind rear seat. No portion of the enclosure may rest on the rear seat while in the fold down position. Any equipment mounted in areas other than the cargo area must be installed in such a way as to not interfere with the normal operation, function, seating, seating capacity, or leg room of the vehicle.
2. Rear vision must not be obscured in any way by any part of the system. The top of the enclosure must be no higher than the top of the rear seats when they are in the factory upright and latched position. Headrests are not considered part of the seat. If the headrest is molded into the seat, the top of the seat is considered the highest spot on the seat where there is a visible difference between the seat and headrest.
3. Pickup trucks: enclosure must not block any 2-way viewable glass. All equipment, excluding batteries, must be mounted in the cab of the truck.
 - a. Standard cab trucks: enclosure must fit behind seat in the most forward position. If aftermarket seats or factory replacement seats are added, and the factory brackets aren't used, then the brackets to hold said seats down must be made to line up with the rear factory bolts as to not increase the area behind said seats.
 - b. Extended cab trucks: enclosure cannot extend past front door jams, but, factory jump seats may be removed
 - c. Quad/Crew cab, with 4 full size doors: the back seat must stay in, but enclosure may sit in seat.
4. All 2 seat non-trunk vehicles: enclosure must be no higher than the bottom of the rear side glass but may not exceed 24" and must be no more than 26" from the center of the top rear door plastic panel. Plastic side panels may not be removed or altered.
5. No podiums allowed, however, head unit may be held outside the vehicle
6. Upgraded electrical and charging systems allowed, however, vehicle is restricted to only one (1) alternator and a maximum of 15.0 volts at the Subwoofer Amplifier(s).
7. Capacitors are allowed. There is no capacitance limit.
8. Only 12-volt batteries, in parallel, are permitted. There is no restriction on the number of batteries.
9. Primary battery may be relocated. All batteries must be securely mounted, and must be located either under the hood and/or in the trunk/hatch/cargo area only. Pick-up trucks may mount batteries in the bed provided they are covered and protected.



- Some unique situations may arise that disqualify vehicle, system, and/or competitor from **Sound Pressure League Street** Division, determined by MECA Judges.